



# 13010 13020 13030 13040 13050 13060 13090 13095 13100 HYDRAULIC RAMS

## Hydraulic Rams

- Used to break rear beads on 5 piece wheels
- Removable plunger adapter allows the use of a variety of threaded attachments
- A must have for OTR wheel and tire service

Model	Capacity	Stroke	Retracted Height
13010	10 Ton	2 -1/8" (5.4 cm)	4-3/4" (12.1 cm)
13020	10 Ton	4" (10.5 cm)	6-3/4" (17.14cm)
13030	10 Ton	6-1/8" (15.57 cm)	9-3/4" (24.77 cm)
13040	10 Ton	8" (20.32 cm)	11-3/4" (29.84 cm)
13050	10 Ton	10-1/8" (25.73 cm)	13- 3/4" (35 cm)
13060	30 Ton	2-7/16" (6.19 cm)	4- 5/8" (11.75 cm)
13090	25 Ton	8-1/4" (21 cm)	12-3/4" (32.39 cm)
13095	25 Ton	10-1/8" (25.73 cm)	14-3/4" (37.4 cm)
13100	25 Ton	6-1/4" (15.75 cm)	10-3/4" (27.3 cm)



2347 Circuit Way  
Brooksville, FL 34604  
352.799.1111 - sales@ameintl.net





# 13010 13020 13030 13040 13050 13060 13090 13095 13100 HYDRAULIC RAMS

## Hydraulic Rams



Scan this QR code for a video demonstration!



2347 Circuit Way  
Brooksville, FL 34604  
352.799.1111 - sales@ameintl.net

