



TIRE LIFE® SERIES

26206, 26207, 26208, 26209

Fuller Brothers™ Tire life® is a premium biodegradable and non-toxic liquid formula developed to benefit all companies that manage commercial fleets. When added to a tire's air chamber, Tire Life® protects tires and eliminates wheel/rim loss from scale and pitting, while improving air retention through its sealing qualities. Labor costs are greatly reduced as tire dismounting time is decreased.

Tire Life® not only reduces tire failures but also aids in the prompt identification of tire cuts and wheel/rim cracks and keeps tires running up to 7.5% cooler than similar tires without the benefit of our product.



26208

- Improves performance in mining, construction, agricultural, and over the road tires
- Protects tire inner liner from degrading
- Protects wheels/rims against rust scale and pitting
- Improves air retention by sealing natural liner porosity, O-rings, bead seats, vent hole leaks, and over-buffed repair areas
- Reduces heat buildup in tires
- Decreases labor time for tire mounting/dismounting
- Safely identifies cracks and leaks in rims – dries light green or yellow when exposed to external air.
- Freeze/thaw stable
- Fluid dynamics provide a tire/wheel balance and vibration damping giving a smoother ride and better tread wear
- No risk of chamber fires
- Certified biodegradable

Model	Description
26206	20-oz Bag of Tire Life®
26207	32-oz Bottle of Tire Life®
26208	6-Gallon Pail of Tire Life®
26209	55-Gallon Drum of Tire Life®





RECOMMENDED QUANTITY CHART FOR OFF-THE-ROAD TIRES

Judging The Correct Quantity

For bias ply off the road tires add 30% more Tire Life® than recommended above. Quantities provided in this application chart are taken from an average.

Each operation is different. Only you can predict your needs accurately.

How To Know You Have The Correct Amount

When the proper quantity has been applied, your tires will dismount easily, rim rust will be eliminated, and the tire inner-liner will benefit from anti-oxidant protection.

Notes

1. For best use, you should make sure your wheels/rims and tires are well cleaned prior to installing Tire Life®. Tire Life® will clean rust and corrosion from your wheels/rims through the natural washing action created by a truck in motion. Tire Life® can be installed with an applicator tank into a mounted assembly without prior cleaning, but then should be checked or changed between 30 to 90 days.
2. A good rule of thumb for judging the correct amount of Tire Life® per tire: If you dismount the tire and have 50% or more of the original install amount left in the tire then you are within good operating tolerances for the effectiveness of Tire Life®.
3. Please contact your Fuller Brothers' Representative if you have any questions or if you would like an on-site assessment and follow up recommendations.

2 GALLONS - 8 LITERS

12.00R24
13.00R24
14.00R24
16.00R24
14.00R25
16.00R25
15.5R25
17.5R25
14.9R24
16.9R24
17.5LR24
19.5LR24

3 GALLONS - 11 LITERS

18.00R25
21.00R25
20.5R25
23.5R25
26.5R25
29.5R25
16.9R28
18.4R28
21LR24

4 GALLONS - 15 LITERS

18.00R33
21.00R35
18.00R49
21.00R49
26.5R29
29.5R29
33.25R29
23.1R26
24.5R32

5 GALLONS - 18 LITERS

24.00R35
33.5R33
29.5R35
33.25R35

6 GALLONS - 23 LITERS

24.00R49
37.5R39
37.25R35
35/65R33
33.5R39
37.5R39
40.5R39
27R56.5

8 GALLONS - 30 LITERS

45/65R45
27.00R49
30.00R51
30R56.5

10 GALLONS - 38 LITERS

33.00R51
36.00R51
37.5R51
50/65R51

15 GALLONS - 57 LITERS

37.00R57
42/90R57

20 GALLONS - 76 LITERS

40.00R57
46/90R57
48/95R57

30 GALLONS - 114 LITERS ALL 63"





TIRE CREAM®

26201, 26202, 26203

- Designed for truck and bus tires, agricultural, forestry, and OTR use
- Excellent O-ring lubricant
- Ready to use cream consistency
- Stays in place: will not cause a mess on your tools, hands, or applicator
- Made to dissipate and clean up with water
- Allows the bead to seat properly
- Sticks to wet beads
- Reduces bead indexing and chipped beads
- Controls bead hardening when used with Tire Life®
- Can store up to 120°F (48.8°C) and -20°F (-28.8°C)
- Will not rust the wheel or wheel parts
- Reduces cleaning of soap-based lubricants and overall wheel cleaning time
- Does not stain aluminum
- Non-toxic, non-hazardous, environmentally safe



26203

26201

26202

Fuller Brothers™ Tire Cream® is a premium quality bead lubricant designed for OTR tires and all other heavy duty industrial applications. Effective uses range from truck and bus tires to agricultural and forestry applications and to Ultra Class OTR. This product is environmentally safe and cleans up with water and soap. Each application only requires a small amount of product to ensure proper mounting and maximum lubrication for efficient bead seating.

Model	Description
26201	16-oz Jar of Tire Cream®
26202	6-lb Pail of Tire Cream®
26203	12-lb Pail of Tire Cream®



WHITE LIGHTNING

26204, 26205

Fuller Brothers™ White Lightning OTR Tire Dismount Lube™ is specially formulated to dismount OTR and commercial truck tires. Slippery formulation aids tire service techs to safely remove tire bead from wheel. Featuring a concentrated 4:1 formulation, White Lightning™ works best when applied through a pressurized sprayer, and it will not etch or damage aluminum wheels. Its ease of use and reliable performance makes it an essential tool for every tire service operation.

- Specially designed for commercial and OTR tires
- Penetrates under bead during deflation
- Drastically improves dismounting and mounting procedures
- Will not etch or damage aluminum wheels
- Dissipates and dries quickly
- Will not leave thick film behind and is water soluble



Model	Description
26204	32-oz Bottle Fuller Brothers™ White Lightning OTR Tire Dismount Lube™
26205	1-Gallon Jug of Fuller Brothers™ White Lightning OTR Tire Dismount Lube™