



Inflation Cage Certification

This certifies that AME International brand inflation cages, part numbers 24420, 24440, 24450, 24430, 24425, 24470, T109, 24459, 24456, and 24458 are designed to meet the requirements for restraining devices outlined in USA OSHA regulation 29 CFR Part 1910.177, so long as all other parts of the regulation are followed. AME International Inflation Cages are rated for 130 psi multi-piece rim wheel separation per OSHA regulation 29 CFR Part 1910.177(d)(3)(i).

Note: The AME International 24456 and 24458 earthmover tire inflation cages are rated for 100 psi. Mere use of a restraining device will not prevent accidents. Proper procedures outlined in OSHA regulation 29 CFR Part 1910.177 must be followed as well as the procedures prescribed by the specific tire and wheel manufacturer.

WARNING:

Tire changing can be dangerous and should be done only by trained personnel using proper tools and equipment as directed by Federal OSHA Standard No. 29 CFR. Tires may explode during inflation causing injury to operator or bystander. **Always refer to the tire and wheel manufacturer's guidelines to understand the proper changing and inflation procedures of the tire and wheel assembly being serviced.**

- Always wear safety glasses.
- Keep all parts of body outside cage.
- Use extension hose, clip-on chuck and remote valve.
- See supervisor for safety precautions.

WARNING:

Do not alter cage in any way. Cage must be freestanding and at least three feet from other objects. Discard cage if bent, cracked, or otherwise damaged.

AME International cages are proudly Made In U.S.A.

Signed: 

Tim Benoist, VP Operations



October, 2023