



HYDRAULIC HOSES AND COUPLERS

Hydraulic Hoses and Couplers

- 10,000 psi (700 bar) working pressure hydraulic hose
- Equipped with 3/8" NPT ends, including one swivel end
- Meets IJ100 Jack Hose specification
- Each hose is tagged with laminated 'Do Not Remove' tags for OSHA compliance

| Hose Length | No Coupler | Hi Flow Male (16050) | Complete Hi Flow (16000) | Quick Connect Female (TC-371) | Complete Coupler (TC-370) |
|-------------|------------|----------------------|--------------------------|-------------------------------|---------------------------|
| 6' | 16116 | 16016 | 16160 | 16116-TC | 16160-TC |
| 8' | 16100 | 16040 | 16030 | 16100-TC | 16030-TC |
| 10' | 16105 | 16045 | 16035 | 16105-TC | 16035-TC |
| 12' | 16120 | 16010 | 16025 | 16120-TC | 16025-TC |
| 18' | 16110 | 16015 | 16020 | 16110-TC | 16020-TC |

Custom sizes available.

High Flow Hydraulic Couplers

- Model 16000 - Complete coupler set
- Interchange with Enerpac C604 and Power Team/OTC 9795
- Plastic Dust cover available, model CD411
- Model 16050 - Male half
- Model 16060 - Female half

Quick Connect Hydraulic Couplers

- 10,000 PSI (700 bar) quick connect coupling, 3/8" NPT
- Parker Series couplings
- Interchange with IMT couplings
- Model TC-370 complete set
- Model TC-371 - Female half
- Model TC-372 - Male half



2347 Circuit Way
Brooksville, FL 34604
352.799.1111 - sales@ameintl.net

